

# ROBUST SEMI-ACTIVE RIDE CONTROL UNDER STOCHASTIC EXCITATION

Jeremy Kolansky- Virginia Tech

Amandeep Singh, Jill Goryca- US Army TARDEC



UNCLASSIFIED: Distribution Statement A. Approved for public release



Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>04 MAR 2014</b>		2. REPORT TYPE <b>Briefing Charts</b>		3. DATES COVERED <b>04-01-2014 to 21-02-2014</b>	
4. TITLE AND SUBTITLE <b>ROBUST SEMI-ACTIVE RIDE CONTROL UNDER STOCHASTIC EXCITATION</b>				5a. CONTRACT NUMBER <b>W56hzv-04-2-0001</b>	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) <b>Jeremy Kolansky; Amandeep Singh; Jill Goryca</b>				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Virginia Polytechnic Institute and State University,222 Burruss Hall,Blacksburg,VA,24061</b>				8. PERFORMING ORGANIZATION REPORT NUMBER <b>; #24517</b>	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) <b>U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000</b>				10. SPONSOR/MONITOR'S ACRONYM(S) <b>TARDEC</b>	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) <b>#24517</b>	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT <b>Briefing charts for SAE 2014</b>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Public Release</b>	18. NUMBER OF PAGES <b>16</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

# Disclaimer

**\*\*Disclaimer:** Reference herein to any specific commercial company, product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the Department of the Army (DoA). The opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or the DoA, and shall not be used for advertising or product endorsement purposes. **\*\***

- Introduction/Overview
- Vehicle Modeling
- Road Profile and Stochastic Excitation
- Performance Metrics
- Control Methodology
- Simulation Results
  - Robust for parameter range
  - Robust for unknown input
  - Comparison
- Conclusions

**Ride comfort for military vehicles are important for several reasons:**

- 1) Fatigue caused by vehicle vibrations**
- 2) Motion sickness reduction by smoothed vehicle motions**
- 3) Ability to modify handling conditions based upon terrain**


**Suspension Type:**

- 1) Fully Active Suspension**
- 2) Passive Suspension**
- 3) Semi-Active Suspension**

**Control Method:**

- 1) LQR/H-Infinity/Linear Methods**
- 2) Nonlinear/Adaptive**
- 3) Discontinuous (Parameterized or otherwise)**

## Seven Degree of Freedom Vehicle Model



### Suspension Forces

$$F_{fl} = k_{fl}(z - a\theta + l\phi - z_{fl}) + c_{fl}(\dot{z} - a\dot{\theta} + l\dot{\phi} - \dot{z}_{fl}) \quad (1)$$

$$F_{fr} = k_{fr}(z - a\theta - r\phi - z_{fr}) + c_{fr}(\dot{z} - a\dot{\theta} - r\dot{\phi} - \dot{z}_{fr}) \quad (2)$$

$$F_{rl} = k_{rl}(z + b\theta + l\phi - z_{rl}) + c_{rl}(\dot{z} + b\dot{\theta} + l\dot{\phi} - \dot{z}_{rl}) \quad (3)$$

$$F_{rr} = k_{rr}(z + b\theta - r\phi - z_{rr}) + c_{rr}(\dot{z} + b\dot{\theta} - r\dot{\phi} - \dot{z}_{rr}) \quad (4)$$

### Wheel Dynamics

$$\ddot{z}_{fl} = \frac{-k_{u,fl} * (z_{fl} - z_{g,fl})H(z_{g,fl} - z_{fl}) + F_{fl}}{m_{fl}} - g \quad (5)$$

$$\ddot{z}_{fr} = \frac{-k_{u,fr} * (z_{fr} - z_{g,fr})H(z_{g,fr} - z_{fr}) + F_{fr}}{m_{fr}} - g \quad (6)$$

$$\ddot{z}_{rl} = \frac{-k_{u,rl} * (z_{rl} - z_{g,rl})H(z_{g,rl} - z_{rl}) + F_{rl}}{m_{rl}} - g \quad (7)$$

$$\ddot{z}_{rr} = \frac{-k_{u,rr} * (z_{rr} - z_{g,rr})H(z_{g,rr} - z_{rr}) + F_{rr}}{m_{rr}} - g \quad (8)$$

### Vehicle Body Dynamics

$$\ddot{z} = \frac{-(F_{fl} + F_{fr} + F_{rl} + F_{rr})}{mass} - g \quad (9)$$

$$\ddot{\theta} = \frac{a(F_{fl} + F_{fr}) - b(F_{rl} + F_{rr})}{J_{pitch}} \quad (10)$$

$$\ddot{\phi} = \frac{-l(F_{fl} + F_{rl}) + r(F_{fr} + F_{rr})}{J_{roll}} \quad (11)$$

# Road Profile and Stochastic Representation

## Third Order Auto Regressive Time-Series Model

$$u_i = \phi_1 u_{i-1} + \phi_2 u_{i-2} + \phi_3 u_{i-3} + \varepsilon_i \quad (12)$$


Feedback Coefficients

$$\phi_1 = 1.2456,$$

$$\phi_2 = -0.2976,$$

$$\phi_3 = -0.1954,$$

$\varepsilon_i = \text{Gaussian White Noise, Unity Variance}$



A series of statistical tests were conducted to examine the validity of the time-series model representation of the road profile

## Third Order Auto Regressive Model

$$u_i = \phi_1 u_{i-1} + \phi_2 u_{i-2} + \phi_3 u_{i-3} + \varepsilon_i \quad (12)$$

Front-Left-Wheel:	$z_{wfl}(t) = z_r(t) = u_i$
Front-Right-Wheel:	$z_{wfr}(t) = z_r(t + \delta) = u_{i+\delta}$
Rear-Left-Wheel:	$z_{wrl}(t) = z_r\left(t + \frac{L}{v_s}\right) = u_{i+\frac{L}{v_s}}$
Rear-Right-Wheel:	$z_{wrr}(t) = z_r\left(t + \frac{L}{v_s} + \delta\right) = u_{i+\frac{L}{v_s}+\delta}$

Wheelbase:  $L$       Vehicle Speed:  $v_s$       Delay:  $\delta$



- **Absorbed Power (At the seat locations)**
  - Next Slide
- **RMS Acceleration (At the seat locations)**
  - $\sqrt{\ddot{z}/N}$
- **Road Holding (At each wheel)**
  - $z_{wheel} - z_{road}$
- **Rattle Space (For each suspension strut)**
  - $z_{body} - z_{wheel}$

- **Absorbed Power**

- Measure of ride comfort
- Amount of energy absorbed from ride vibration

$$\overline{AP} = \lim_{T \rightarrow \infty} \frac{1}{T} \int_0^T F(t)V(t)dt$$

- Actual absorbed power with physical characteristics
- Typical coefficients of a 50th percentile man are used
- For the 7-DOF model, the absorbed power is computed at all the four seats (two in front and two in rear), and averaged to represent a single ride comfort metric used for the study.





# Control Methodology – Accelerometer Driven Damper (ADD)

## Infinite Control Authority ADD


$$C_{desired} = C_{min} + H(\ddot{z}_{def})(C_{max} - C_{min}) \quad (13)$$

## Moving Average Filter


$$z_k = \sum_{i=0}^N \frac{1}{N+1} z_{k-i} \quad (14)$$



# Simulation Results – Parameter Effects




# Simulation Results – Parameter Effects




# Simulation Results – Stochastic Road Effects

Response Surface for Varying Sliding Window Length and Road Roughness, 15 MPH




# Simulation Results – Stochastic Road Effects

Response Surface for Varying Sliding Window Length and Road Roughness, 30 MPH




# Simulation Results – Ride Comfort Comparison

Comfort Performance for Smoothed ADD Control



Comfort Performance for Original ADD Control



Quarter Car Results	Average Absorbed Power (W)	Sprung Mass Acceleration RMS (g's)	Road Holding Max (in)
Passive	26.65	0.61	4.45
SH 2-state	6.19	0.39	4.87
SH-ADD	3.43	0.25	4.87
SH Linear	3.05	0.23	5.54
ADD	1.28	0.19	5.11
Smoothed ADD (Proposed)	1.09	0.17	5.18



# Conclusions

- Smoothing function significantly improves over the original ADD control for the higher fidelity models than just quarter car models.
- Invariant with respect to vehicle mass/inertia (Does not require any vehicle parameters)
- Invariant with respect to road profile
- Computationally efficient algorithm. Challenge comes from sensor implementation